



***Flammability rating 94V-2
Weather and UV Resistant
High Strength Locking
CE and UL Approved***

www.himel.com

Founded in Spain in 1958

Cable Ties



The unmissable product for electricians

Commercial Reference	Parameters						Details	
CableTies	Length (mm)	Width (mm)	Color	Material	Max Bundle Diameter	Tensile Strength (LBS)	Carton	Bag
HHEC1025B	100	2.5	Black	Nylon 66	22	18	500	100
HHEC1025W	100	2.5	White	Nylon 66	22	18	500	100
HHEC1535B	150	3.5	Black	Nylon 66	35	40	250	100
HHEC1535W	150	3.5	White	Nylon 66	35	40	250	100
HHEC2048B	200	4.8	Black	Nylon 66	50	49	150	100
HHEC2048W	200	4.8	White	Nylon 66	50	49	150	100
HHEC2536B	250	3.6	Black	Nylon 66	65	40	150	100
HHEC2536W	250	3.6	White	Nylon 66	65	40	150	100
HHEC3048B	300	4.8	Black	Nylon 66	82	49	100	100
HHEC3048W	300	4.8	White	Nylon 66	82	49	100	100
HHEC3548B	350	4.8	Black	Nylon 66	90	49	80	100
HHEC3548W	350	4.8	White	Nylon 66	90	49	80	100
HHEC1025C1500	100	2.5	colorful	Nylon 66	22	18	8	1500
HHEC1535C800	150	3.5	colorful	Nylon 66	35	40	8	800