

Product data sheet

HA VSP4T0220P

Characteristics

Variable speed drive, SMART Pump, 22 kW, 380 V, 3 phase, normal duty



Main

| | |
|------------------------------------|---|
| Range of product | SMART-Pump |
| Product or component type | Variable speed drive |
| Product specific application | Pump Fan Chiller |
| Network number of phases | 3 phases |
| [Us] rated supply voltage | 380...440 V - 15...10 % |
| Supply frequency | 50...60 Hz |
| Motor power kW | 22 kW for normal duty |
| Motor power hp | 30 hp for normal duty |
| Maximum transient current | 54 A during 1 min (normal duty) 67.5 A during 1 s (normal duty) 81 A during 0 s (normal duty) |
| Asynchronous motor control profile | Sensorless vector control (SVC) Voltage/frequency ratio (V/f) |
| Speed drive output frequency | 0...599 Hz |
| Continuous output current | 45 A |
| EMC filter | Class C3 EMC filter |

Complementary

| | |
|-------------------------------------|--|
| Product destination | Asynchronous motors |
| Function available | Multi-pump control Dry run protection Energy/flow calculator Frost and condensation protection Pump cleaning Fire override mode Energy saving mode |
| Type of cooling | Fan |
| Communication port protocol | Modbus |
| Regulation loop | Adjustable PID regulator with sleep mode |
| Acceleration and deceleration ramps | Linear adjustable separately from 0.01 to 3600 s |
| Frequency resolution | Digital input: 0.005/50 Hz Analog input: 0.05/50 Hz |
| Analogue input number | 2 |
| Analogue input type | AI1 voltage: 0...10 V, impedance: 100 kOhm, resolution 0.01 V AI1 current: 0...20 mA, impedance: 500 Ohm, resolution 0.02 mA AI2 voltage: 0...10 V, impedance: 100 kOhm, resolution 0.01 V AI2 current: 0...20 mA, impedance: 500 Ohm, resolution 0.02 mA |
| Discrete input number | 5 |
| Discrete input type | Programmable (DI1...DI5) Programmable as pulse input (DI5) |
| Analogue output number | 2 |

| | |
|---------------------------------------|---|
| Analogue output type | AO1 voltage/current: 0...20 mA or 0...10 V AO2 voltage/current: 0...20 mA or 0...10 V |
| Discrete output number | 3 |
| Discrete output type | configurable relay logic 250 V (5 A) for NO relay output circuit configurable relay logic 250 V (3 A) for NC relay output circuit configurable relay logic 24 V DC (3 A) for NO relay output circuit configurable relay logic 24 V DC (3 A) for NC relay output circuit open collector 9...30 V (50 mA) open collector 9...30 V (50 mA) for pulse output |
| Output frequency | 50 kHz for pulse output at DO2 |
| Display type | 5 digits 7 segments for 38 parameters |
| Device application | Speed control |
| Device composition | Built-in breaking unit |
| Type of installation | Indoor/outdoor |
| Control type | Manual using keypad Using control terminal Using serial port |
| Device mounting | Wall mounted Enclosure Flange |
| Speed accuracy | +/- 0.1 % of nominal speed |
| Protection type | Hammer effect Overcurrent Overvoltage Undervoltage Overheating Overload Short-circuit |
| Width | 205 mm |
| Height | 322 mm |
| Depth | 215 mm |
| Environment | |
| Relative humidity | 0...95 % without condensation |
| Ambient air temperature for storage | -20...60 °C |
| Quality labels | CE |
| Operating altitude | = 1000 m |
| IP degree of protection | IP20 |
| Ambient air temperature for operation | -10...40 °C |
| Environmental characteristic | Dust resistant Corrosive gas free Oil and vapour resistant |
| Vibration resistance | 5.9 m/s ² |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |